TEST FLIGHTS AND ALTITUDE CONTROL DEMONSTRATION OF A PROTOTYPE VENUS AEROBOT

Jacob Izraelevitz¹, Michael Pauken¹, Siddharth Krishnamoorthy¹, Ashish Goel¹, Carolina Aiazzi¹, Blair Emanuel¹, Gerald Walsh¹, Leonard Dorsky¹, Stacy Weinstein-Weiss¹, Alex Austin¹, Kevin Baines¹, Paul K. Byrne³, James Cutts¹, Caleb Turner², Carlos Quintana², Kevin Carlson², Tim Lachenmeier², and Jeffery Hall¹.

¹NASA Jet Propulsion Laboratory, California Institute of Technology (4800 Oak Grove Drive, Pasadena, CA 91109)

Introduction: The clouds of Venus offer a unique extraterrestrial environment: ample sunlight, Earth-like temperatures and pressures, and strong zonal winds that can carry an in situ aerial platform around the planet in just a few Earth days. This cloud layer is key to moderating the solar radiative balance of the planet, the transport of materials between the atmosphere and the ground, and the interactions (physical, chemical, and possibly biological) between atmospheric constituents. The two VeGa balloon flights in 1985 [1], launched by the Soviet Union, successfully flew in the Venus clouds using superpressure balloons, which nominally have a relatively fixed buoyancy and provide access to only a single altitude.

JPL is pursuing the technologies required to design a buoyant "aerobot" (aerial robotic balloon), with a lifetime of months, to perform targeted science in the Venus clouds (Figure 1). Because of the extremely strong and consistent zonal winds on Venus, any aerobot is expected to circumnavigate the planet passively every 5 to 7 Earthdays. In contrast to its VeGa predecessors, the JPL aerobot is a controllable variable-altitude balloon [2]—providing access to a broad altitude range over the course of the flight, and a consequently increased science return [3].

This science return advantage has been well received by the Venus community. In preparation for the 2023–2032 Planetary Science and Astrobiology Decadal Survey, NASA commissioned two mission studies that elected to utilize a variable-altitude aerobot for Venus: a many-asset Venus Flagship Mission (VFM) [4] and an aerial platform with orbiter mission under New Frontiers [5].

Objective: The objective of this work is to develop the variable-altitude Venus technology for a competed-mission aerobot [6], see accompanying *Phantom* abstract [7]. The architecture consists of two balloons: an outer, metallized Teflon-coated unpressurized balloon (which protects against sulfuric acid aerosols and sunlight), and an inner Vectran-reinforced pressurized balloon that serves acts as a helium reservoir. Transferring helium between the inner and outer balloons modulates the buoyancy and altitude. For Venus, an aerobot of 12–15 m diameter [8] is necessary for a carrying capacity of 100–200 kg, consistent with a major scientific investigation of and from the cloud layer, with a 10 km-wide altitude-control capability nominally from 52 km to 62 km.



Figure 1: Prototype one-third-scale Venus aerobot in flight above the Blackrock desert, Nevada. The aerobot includes a metalized-Teflon outer envelope and an internal helium reservoir.

²Near Space Corporation (5755 Long Prairie Road Tillamook, OR 97141)

³Washington University in St. Louis (1 Brookings Dr, St. Louis, MO 63130)

Results: We will discuss the subscale prototype fabrication and test flight efforts pursued as a collaboration between JPL and Near Space Corporation. Two prototypes have been built so far [8,9] at approximately 1:3 scale to the Venus design points, with a third prototype in progress. These prototypes are of increasingly higher fidelity, with balloon envelopes and seams capable of withstanding the high-temperature (~100°C), high-pressure loads (~30 kPa), sulfuric-acid environment (94% concentration), and solar radiative heating (2300 W/m²) environmental conditions that will be encountered when needed for flight flying in the Venus cloud layer. We will report on two recent test flights of these prototypes on Earth (Figure 2) at atmospheric densities equivalent to 54-55 km above the Venus surface, the coupon-level testing of balloon materials (Figure 3), and the application of these results to the performance at full scale on Venus.



Figure 2: Launch photographs of prototype Venus aerobot during July 2022 test flight campaign. Top: aerial view of first flight in direct sunlight. Bottom: second flight in sunrise radiative flux conditions.




Figure 3: Material coupon test of exterior balloon seam, where a witness paper is protected from acid of same aerosol attributes as present at 52km altitude on Venus.

Acknowledgements: The research described in this paper was funded by the Jet Propulsion Laboratory, California Institute of Technology, under a contract with the National Aeronautics and Space Administration.

References:

- [1] Huntress, Wesley T., and Mikhail Ya Marov. Soviet Robots in the Solar System: Mission Technologies and Discoveries. Springer Science & Business Media, 2011.
- [2] Hall, Jeffery L., et al. "Altitude-Controlled Light Gas Balloons for Venus and Titan Exploration." AIAA Aviation 2019 Forum. 2019-3194.
- [3] Venus Aerial Platforms Study Team, "Aerial Platforms for the Scientific Exploration of Venus", JPL D-102569, October, 2018.
- [4] Gilmore, Martha et al. "Venus Flagship Mission Planetary Decadal Study, a Mission to the Closest Exoplanet." Exoplanets in Our Backyard: Solar System and Exoplanet Synergies on Planetary Formation, Evolution, and Habitability. 2020
- [5] O'Rourke et al. (2021), "ADVENTS: Assessment and Discovery of Venus' Past Evolution and Near-Term Climatic and Geophysical State".
- [6] Cutts, Jim, et al. "Exploring the Clouds of Venus: Science Driven Aerobot Missions to our Sister Planet." 2022 IEEE Aerospace Conference. IEEE, 2022.
- [7] Byrne, P. K. et al. (2023) *LPS*, 54, this mtg.
- [8] Hall, Jeffery L., et al. "Prototype Development of a Variable Altitude Venus Aerobot." AIAA Aviation 2021 Forum. 2021-2696.
- [9] Izraelevitz, Jacob, et al. "Subscale Prototype and Hangar Test Flight of a Venus Variable-Altitude Aerobot." 2022 IEEE Aerospace Conference. IEEE, 2022.